

承认书

SPECIFICATION FOR APPROVAL

Part No. HWA804V6FA-B
Description:
Revision: 1.3
Customer.
Customer Approval No. :

承认鉴章后请寄回承认书正本一份

Please return to us one original of “SPECIFICATION FOR APPROVAL” with your approved signatures.

承认书 APPROVED SIGNATURES	
使用方	承制方
核准人 APPROVED BY: 日期 DATE: 盖章签署 CHOP & SIGNATURES:	核准人 APPROVED BY: 日期 DATE: 盖章签署 CHOP & SIGNATURES:

深圳市华云电源有限公司

SHENZHEN HWAWAN POWER CO. LTD.

深圳市南山区西丽沙河西路 5298 号百旺研发大厦 1 栋 10 楼 1020 室

Room 1020, 10/F, Building 1, Baiwang Research and develop Mansion, No.5298, Shahe West Road, Xili, Nanshan, Shenzhen, Guangdong.

电话 Tel: (86) 755-22678080

传真 Fax: (86) 755-22678082

公司网址 Web: [Http://www.hwa-power.com](http://www.hwa-power.com)

HWA804V6FA-B

■ High-efficiency Switching Power Supply product

HWA804V6FA-B is a High-efficiency power supply with a rated output of 4.6V / 80A, designed for LED display products. The power supply has a current sharing function and can be used in parallel. The power supply has the following characteristics:

- ◆ The power supply has a current sharing function and can be used in parallel
- ◆ The power supply has a Power Good signal which can be used to detect the operating status of the power supply
- ◆ Small size: 284mm*57mm*26mm(L*W*H)
- ◆ Light weight : ≤550g
- ◆ High efficiency: 89%(@Input 220VAC,Output4.6V/40-60A)
- ◆ Small Leakage current: <1mA
- ◆ Output voltage can be adjusted from 4.2V to 4.6V
- ◆ EMI standard: EN55032 CLASS A
- ◆ Wide operating temp. range: -25~+80℃(Shell temperature)
- ◆ Wide Input voltage range: 90VAC~264VAC
- ◆ Power factor: ≥0.95
- ◆ Cooling mode: conduction cooling
- ◆ Output over-voltage protection
- ◆ Output over-current protection
- ◆ Output short-circuit protection
- ◆ Over temperature protection
- ◆ Compliance with UL, CE, CB,CCC certifications



Product Picture



NOTES:

1. The final installation environment of the product needs to meet the environment where the heat sink is simulated. (Refer to fig. 4 for the aluminum radiator size.)
2. The indicators in this specification are the results of testing under the recommended environment. That is, the power supply must be installed on a heat sink with the size of 500*250*6mm.
3. Warning: In a residential environment, running this device may cause radio interference.

safety rule

 High voltage	Power input port with high voltage, cannot be touched by hand (Port d'entrée d'alimentation à haute tension, ne peut pas être touché à la main)
 Warning	The power supply is a product with large leakage current. Please ground reliably before powering on. When install the product, the metal enclosure needs to be reliably earthed, and the earthing connection is to be evaluated in the end installation. (L'alimentation est un produit avec un fort courant de fuite. Veuillez mettre à la terre de manière fiable avant de mettre sous tension)
 High voltage	It is strictly forbidden to carry out high voltage and alternating current operation under thunderstorms (Il est strictement interdit d'effectuer des opérations à haute tension et à courant alternatif sous des orages)

1. Specifications


Environmental Requirements					
Parameter	Min.	Typ.	Max.	Unit	Remark
Operating Temperature	-25	65	+80	°C	The test point is 60mm from the output end to the center of the upper cover of the power supply housing.
Storage Temperature	-30	+25	+90	°C	/
Humidity	5	/	95	%	Relative humidity, no condensing
Altitude	0	/	4000	m	/
Cooling	/	/	/	/	conduction cooling

Input Characteristics					
Parameter	Min.	Typ.	Max.	Unit	Remark
Input Voltage Range	90	110/220	264	Vac	/
Input Voltage Frequency	47	50/60	63	Hz	/
Power Factor	0.95	/	/	/	@220Vac,full load
Input Inrush Current	/	/	80	A	@220Vac,full load & Cold state
AC Input Mode	/	Single phase input (L、N)	/	/	/

Output Characteristics					
Parameter	Min.	Typ.	Max.	Unit	Remark
Output Voltage Range	4.2	4.6	4.6	Vdc	Adjustable
Output Voltage Setpoint	X-0.05	X	X+0.05	Vdc	'X' is the typical value set according to customer's request.
Output Current	0	/	80	A	Universal input (refer to fig.1 & fig.2)
Load Regulation	/	/	± 1	%	Rated voltage input, load changing from min. to max.
Output voltage accuracy	/	/	± 2	%	Universal input, full load
Line Regulation	/	/	± 0.5	%	Full range of input voltage, full load
Degree of Current Sharing Imbalance	/	5	/	%	The total output current is greater than 50% of the total maximum output current. Note 1*
Power Good	2.6	2.8	3.0	V	While the output voltage is normal
	/	/	0.5	V	While the output voltage is abnormal
Ripple and Noise (V _{peak-peak})	/	/	200	mV	Full range of input voltage & load condition, with one 0.1 μ F film capacitor and one 10 μ F high frequency electrolyte capacitor in parallel with the end of sensor lines. Use twisted pair with length of 30 ± 2 cm as the sensor lines. Oscilloscope band width shall be set to 20MHz, and need to remove the probe cap and ground clamp.

HWA804V6FA-B Output Graphs


1) Load - ambient temperature de-rating curve



(figure 1)

Power supply is installed on the radiator of 500*250*6 (base plate 3mm tooth height 3mm)

2) Input voltage - load de-rating curve



(figure 2)

Power supply is installed on the radiator of 500*250*6 (base plate 3mm tooth height 3mm)

1. Specifications

Miscellaneous					
Parameter	Min.	Typ.	Max.	Unit	Remarks
Efficiency	86	88	/	%	@25°C, 220Vac input, output :4.6V/80A
Dynamic response 1	/	/	±5	%	Load variation: 25%-50%-25% or 50%-75%-50% Rate: 1A/us, Period: 4ms
Dynamic response 2	/	/	±10	%	Load variation: 5%-100%-5% Rate: 1A/us, Period: 10ms
Temperature coefficient	/	/	±0.02	%/°C	Universal input, full load
Turn On Delay Time	/	/	2	S	Full range of input voltage & load condition
Over/under shoot @ start -up/shutdown	/	/	±10	%	Full range of input voltage & load condition
Rise Time	/	/	100	ms	Rated input, full load
Capacitive loading	8000	/	20,000	μF	For LED display product, we recommend that the extra electrolyte capacitor's value should be not less than 2,200μF for per 10A output current.

Protections					
Parameter	Min.	Typ.	Max.	Unit	Remarks
Output Over Voltage Protection	5.5	/	6	V	Hiccup Mode
Output Over Current Protection	85	/	110	A	Hiccup Mode
Output Short-circuit Protection	/	/	/	/	Long-term short-circuit endurable. Auto recovery
Over Temperature Protection	90	/	100	°C	Over temperature shutdown, recover automatically. The test point is the surface center of the power supply cover.

1. Specifications


EMC and other parameters		
Item	Level	Standard
CE	CLASS A	EN55032
RE	CLASS A	EN55032
SURGE	Input level B(1.2/50us) line-line : 1kV line-PGND: 2kV	IEC61000-4-5
ESD	level B Contact discharge: $\pm 4\text{kV}$ Air discharge: $\pm 8\text{kV}$	IEC61000-4-2
CS	LEVEL 3; level A; 10V	IEC61000-4-6
RS	Level 3 ; level A; 10V/m	IEC61000-4-3
Immunity to Electrical Fast Transient	$\pm 2\text{kv}$, LEVEL 3, level B	IEC61000-4-4
Voltage fluctuation and Flicker	$P_{st} \leq 1.0$, $P_{lt} \leq 0.65$, $dc \leq 3\%$, $d_{max} \leq 4\%$ the value of $d(t)$ during a voltage change shall not exceed 3% for more than 200ms	IEC61000-3- 3
Harmonic Current Emission	CLASS A	IEC61000-3- 2 [6]
Audible Noise	45dB(A)	Test distance:1m
MTBF	$\geq 100,000\text{hrs}$ @ half load/25°C	
Vibration	Frequency 1-4Hz, acceleration spectral density $0.0001\text{g}^2/\text{Hz}$. Frequency 4-100Hz, acceleration spectral density $0.01\text{g}^2/\text{Hz}$. Frequency 100-200Hz, acceleration spectral density $0.001\text{g}^2/\text{Hz}$. Total rms acceleration: 0.781Grms. Test axis Direction: 3 axes. Test time: 30 min per axis.	
Shock	Half sine wave. Peak acceleration: 300m/s^2 . Pulse width: 6ms. Axis Direction: 6 directions. 3 shocks on each direction.	
Odor	No peculiar and deleterious odor	

Insulation rating		
Parameter	Requirement	Remark
Input - Output	3000Vac/10mA//1min	No flashover or breakdown
Input - Chassis	1500Vac/10mA//1min	
Output - Chassis	500Vdc/10mA//1min	
Leakage Current	$< 1\text{ mA}$	240Vac/50Hz Input
Grounding Resistance	$< 0.1\ \Omega$	Test condition: 40A/2mins
Insulation Resistance	@ Normal atmospheric pressure, relative humidity: 90% Testing voltage: 500V dc Insulation of primary-secondary, primary-ground, secondary-ground shall not be less than $10\text{M}\Omega$	

2. Mechanical

Mechanical specifications	
Length (mm)	284 ±0.5
Width (mm)	57±0.5
Height (mm)	26±0.7
Weight (g)	≤550

Dimensions and mounting holes - terminal coordinates



3. Signal



J1 安装示意图

J2 安装示意图

Function Connector(J1):

Signal	Pin No.	Assignment
J2 Even Flow Pin	1	P.G(Power Good)
	2	GND
	3	SHARE+
	4	NC